
Reynolds Cycle Technology (2000) Ltd

Cycle Frame Tube Stock Price List - January 2006

953 tubing/fittings - US\$ prices

The prices included in this list are subject to our standard conditions of sale.

All prices are Chino, CA

Payment terms to be agreed

Contacts

Sales / Technical -

info@fairing.com

Manufactured by:

Reynolds Cycle Technology, Redfern Road, Tyseley, Birmingham B11 2BS

Tel +44 (0)121 706 5151, Fax +44 (0)121 707 0081

weight
NB uncut length

953 frame kits

PART NO	Diameter mm	Wall mm	Length mm	Butt Profile mm	Weight gms
953 FRAME TUBES - SUFFIX D					
Drawn , NOT heat-treated prior to despatch					
SS4000D	28.6	0.5/0.3/0.5	600	40.40.380.40.100	149
SS4010D	28.6	0.5/0.3/0.5	600	75.50.280.50.145	162
SS4020D	28.6	0.55/0.35/0.55	625	120.50.320.50.85	190
SS4070D	28.6	0.6/0.4	635	125.75.435	198
SS4100D	31.75	0.55/0.35/0.55	635	40.40.400.40.130	200
SS4110D	31.75	0.6/0.4/0.6	650	40.40.400.40.130	231
SS4120D	31.75	0.6/0.4/0.6	650	120.50.300.50.130	245
SS4130D	31.75	0.55/0.35/0.55	650	120.50.300.50.130	220
SS4200D	34.9	0.55/0.35/0.55	680	40.40.420.40.140	238
SS4210D	34.9	0.6/0.4/0.6	680	40.40.420.40.140	267
SS4220D	34.9	0.6/0.4/0.6	680	120.30.320.30.180	285
SS4230D	34.9	0.65/0.45/0.65	680	120.30.320.30.180	313
SS4300D	36.4	0.6/0.45/0.6	685	120.50.300.50.165	315
SS4310D	37.3	0.65/0.5/0.65	685	120.50.300.50.165	338

PART NO	Diameter mm	Wall mm	Length mm	Butt Profile mm	Weight gms
	Shaped Tubing			BASED ON PART	
SS4700D	31.7->28.6	swaged 31.7mm		SS4120D	235
SS4710D	34.9->31.7	swaged 34.9mm		SS4220D	275

SS4720D	Teardrop 34.9	full length		SS4220D	285
SS4730D	31.7 OVAL	full length 35/26		SS4100D	200
SS4732D	31.7 Bi-Oval	90 degree opposed oval		SS4120D	245
SS4740D	34.9 OVAL	full length 40/30		SS4210D	267
SS4742D	34.9 Bi-Oval	90 degree opposed oval		SS4220D	285

Please ask for other alternatives or custom shapes

chainstay in 953 - butted

FS4510D	20/31 oval	0.7/0.5	410	taper to 15mm tip in 953	146
Head tube					
HS4400D	38.1	0.7	200		129
HS4410D	38.1	0.7	600		386

953 FRAME TUBES - SUFFIX A

Drawn , AND AGED prior to despatch

SS4000A	28.6	0.5/0.3/0.5	600	40.40.380.40.100	149
SS4010A	28.6	0.5/0.3/0.5	600	75.50.280.50.145	162
SS4020A	28.6	0.55/0.35/0.55	625	120.50.320.50.85	190
SS4070A	28.6	0.6/0.4	635	125.75.435	198
SS4100A	31.75	0.55/0.35/0.55	635	40.40.400.40.130	200
SS4110A	31.75	0.6/0.4/0.6	650	40.40.400.40.130	231
SS4120A	31.75	0.6/0.4/0.6	650	120.50.300.50.130	245
SS4130A	31.75	0.55/0.35/0.55	650	120.50.300.50.130	220
SS4200A	34.9	0.55/0.35/0.55	680	40.40.420.40.140	238
SS4210A	34.9	0.6/0.4/0.6	680	40.40.420.40.140	267
SS4220A	34.9	0.6/0.4/0.6	680	120.30.320.30.180	285
SS4230A	34.9	0.65/0.45/0.65	680	120.30.320.30.180	313

PART NO	Diameter mm	Wall mm	Length mm	Butt Profile mm	Weight gms
SS4300A	36.4	0.6/0.45/0.6	685	120.50.300.50.165	315
SS4310A	37.3	0.65/0.5/0.65	685	120.50.300.50.165	338

Shaped Tubing			BASED ON PART	
SS4700A	31.7->28.6	swaged 31.7mm	SS4120A	235
SS4710A	34.9->31.7	swaged 34.9mm	SS4220A	275
SS4720A	Teardrop 34.9	full length	SS4220A	285
SS4730A	31.7 OVAL	full length 35/26	SS4100A	200
SS4732A	31.7 Bi-Oval	90 degree opposed oval	SS4120A	245
SS4740A	34.9 OVAL	full length 40/30	SS4210A	267
SS4742A	34.9 Bi-Oval	90 degree opposed oval	SS4220A	285

Please ask for other alternatives or custom shapes

chainstay in 953 - butted

FS4510A	19/31 oval	0.7/0.5	410	taper to 15mm tip in 953	146
---------	------------	---------	-----	--------------------------	-----

Head tube

HS4400A	38.1	0.7	200		129
HS4410A	38.1	0.7	600		386

OTHER FRAME TUBES

CHAINSTAYS in 316L

FS4500	19/31 oval	0.7	410	taper to 15mm tip	170
--------	------------	-----	-----	-------------------	-----

SEATSTAYS IN 316L

GS4600	19.05	0.55	580	taper to 13mm tip	144
--------	-------	------	-----	-------------------	-----

PART NO	Diameter mm	Wall mm	Length mm	Butt Profile mm	Weight gms
----------------	--------------------	----------------	------------------	------------------------	-------------------

FRAME FITTINGS

MTL CODE

LS100A	BB Shell	OD 38.1mm, thread 24TPI	68mm wide		953
LS110A	BB Shell	OD 38.1mm, thread 24TPI	68mm wide		920
LS150A	Rear Dropouts(PR)	Standard 3.8mm slot		C/S tip = 15mm, S/S=13mm	953
LS160A	Rear Dropouts(PR)	Lightweight 2.9mm slot,		C/S tip = 15mm, S/S=13mm	953

		3.8mm at QR/qxle		
LS200A	Cable guides	set of 3	SET OF 3	920
LS210A	STI bosses	set of 2	SET OF 2	920
LS220A	Campy bosses	set of 2	SET OF 2	920
LS225A	Campy bosses	set of 2	SET OF 2	304
LS230A	Head tube cups	set of 2 - integrated style	SET OF 2	304
LS240A	Head tube cups	set of 2 - 34.mm ID	SET OF 2	953
LS245A	Head tube cups	set of 2 - 34.mm ID	SET OF 2	920
LS250A	Brake bridge	Standard allen key fit	EA	920
LS255A	Brake bridge	Standard allen key fit	EA	304
LS260A	Seat clamp	for 28.6mm OD	EA	920
LS265A	Seat clamp	for 31.7mm OD	EA	920

note: For Fittings, MTL CODE is stainless steel:

953 for MARAGING steel, 920 for Custom 630 type, or 304 alloy