

**REYNOLDS STANDARD RANGE OF STEEL, TITANIUM AND ALUMINIUM BUTTED FRAME TUBES,
FORK BLADES AND REAR STAYS**

| Part number | Outside Diameter (mm) | Gauge (thickness) mm | Length mm | Description or butt profile (mm) |
|-------------|-----------------------|----------------------|-----------|----------------------------------|
|-------------|-----------------------|----------------------|-----------|----------------------------------|

STEEL FRAME TUBES

Reynolds 853 PROTEAM series

| | | | | |
|--------|-------|----------------|-----|-------------------|
| AX2000 | 25.4 | 0.6/0.4/0.6 | 600 | 100.50.300.50.100 |
| BX2056 | 28.6 | .65/.45/.65 | 635 | 40.40.380.40.135 |
| BX2103 | 31.75 | 0.65/0.45/0.65 | 650 | 100.50.335.50.115 |
| BX2117 | 31.75 | 0.7/0.5/0.7 | 650 | 40.40.400.40.130 |
| BX2152 | 34.9 | 0.7/0.5/0.7 | 650 | 40.40.420.40.110 |
| BX2162 | 37.3 | 0.8/0.5/0.8 | 650 | 120.50.300.50.10 |

shaped top / down tube

| | | | | |
|--------|---------|-------------|-----|----------------|
| BX2706 | 22 x 40 | 0.7/0.5/0.7 | 650 | flat side oval |
| BX2709 | 34 x 28 | 0.7/0.5/0.7 | 650 | oval |

opposed oval

| | | | | |
|--------|---------|-------------|-----|--------------|
| BX2805 | 34 x 28 | 0.7/0.5/0.7 | 635 | opposed oval |
| BX2800 | 30 x 40 | 0.8/0.5/0.8 | 635 | opposed oval |

teardrop

| | | | | |
|--------|---------|-------------|-----|--------------------|
| AX2605 | 44 x 32 | 0.9/0.6/0.9 | 635 | teardrop |
| AX2606 | 40 x 26 | 0.7/0.5/0.7 | 650 | flat side teardrop |

seat tubes

| | | | | |
|--------|-----------------|--------------|-----|--------------------------------|
| CX2210 | 28.6 | 0.8/0.4/0.6 | 635 | 180.50.230.50.140.-27.2 pillar |
| CX2216 | 28.6 | 0.8/0.6/1.05 | 650 | 115.35.340.45.115 (bulge) |
| BX2185 | 31.7 tt 27.2 id | 0.8/0.55 | 680 | 125.75.435 |

Reynolds 853

Frame tubes

| | | | | profile |
|---------|-------|--------------------|-----|-------------------------------|
| BX2050L | 28.6 | 0.75/0.45/0.75 | 680 | 75.50.280.50.225 |
| BX2060 | 28.6 | 0.8/0.5/0.8 | 635 | 100.50.300.50.135 |
| BX2106 | 31.75 | 0.7/0.5/0.7 | 680 | 75.50.280.50.225 |
| BX2110L | 31.75 | 0.8/0.5/0.8 | 680 | 120.50.300.50.160 |
| BX2156 | 34.9 | 0.8/0.5/0.8 | 680 | 120.30.320.30.180 |
| BX2151 | 34.9 | 0.9/0.6/0.9 | 680 | 120.30.320.30.135 |
| BX2160 | 37.3 | 0.9/0.6/0.9 | 635 | 120.50.300.50.115 |
| CX2201 | 28.6 | 0.7/0.5 | 635 | 125.75.435 |
| CX2361 | 28.6 | 0.9/0.6/1.2 bulged | 400 | 150.80.60.50.60 bulge 27.2 |
| CX2362 | 28.6 | 0.9/0.6/1.2 bulged | 450 | 125.80.95.50.100 bulge 27.2 |
| CX2363 | 28.6 | 0.9/0.6/1.2 bulged | 550 | 170.50.155.75.100 bulge 27.2 |
| CX2364 | 28.6 | 0.9/0.6/1.2 bulged | 650 | 190.50.260.50.100 bulge 27.2 |
| CX2280 | 31.75 | 0.9/0.6/1.2 bulged | 550 | 165.50.260.30.125 - 30 pillar |

Shaped top / down tube

| | | | | |
|--------|---------|-------------|-----|------------|
| BX2705 | 30 x 40 | 0.8/0.5/0.8 | 635 | full oval |
| BX2905 | 30 x 40 | 0.8/0.5/0.8 | 635 | taper oval |

Reynolds 725 series rear stays are recommended with 853 main tubes

| Part number | Outside Diameter (mm) | Gauge (thickness) mm | Length mm | Description or or butt profile (mm) |
|-------------|-----------------------|----------------------|-----------|-------------------------------------|
|-------------|-----------------------|----------------------|-----------|-------------------------------------|

853 continued

Head tubes

| | | | | |
|--------|-------|------|-----|--|
| DX2300 | 31.75 | 0.9 | 220 | |
| DX2320 | 32.5 | 1.25 | 200 | |
| DX2340 | 36.4 | 1.2 | 200 | |

Reynolds 725

Frame tubes

| | | | | |
|-------|-------|--------------------|-----|-------------------------------|
| AG103 | 25.4 | 0.7/0.4/0.7 | 600 | 75.50.280.50.145 |
| AG208 | 28.6 | 0.7/0.4/0.7 | 680 | 75.50.280.50.225 |
| AG206 | 28.6 | 0.8/0.5/0.8 | 635 | 75.50.280.50.180 |
| AG201 | 28.6 | 0.9/0.6/0.9 | 635 | 75.50.280.50.180 |
| AG304 | 31.75 | 0.8/0.5/0.8 | 635 | 120.50.300.50.115 |
| AG301 | 31.75 | 0.9/0.6/0.9 | 635 | 120.50.300.50.115 |
| AG505 | 34.9 | 0.8/0.5/0.8 | 635 | 120.50.300.50.115 |
| AG503 | 34.9 | 0.9/0.6/0.9 | 680 | 120.30.300.30.200 |
| AG510 | 37.3 | 0.9/0.6/0.9 | 635 | 120.50.295.50.120 |
| AG401 | 28.6 | 0.9/0.6 | 635 | 100.75.460 |
| AG403 | 28.6 | 0.8/0.5 | 635 | 125.75.435 |
| AG455 | 28.6 | 0.9/0.6/1.2 bulged | 550 | 170.50.155.75.100 -bulge 27.2 |
| AG457 | 28.6 | 0.9/0.6/1.2 bulged | 635 | 195.50.260.30.100 -bulge 27.2 |

Shaped top / down tubes

| | | | | |
|--------|---------|-------------|-----|----------|
| AG2600 | 50 x 32 | 0.9/0.6/0.9 | 650 | teardrop |
| AG2605 | 49 x 28 | 0.9/0.6/0.9 | 635 | teardrop |

Head tubes

| | | | | |
|--------|-------|------|-----|--|
| DG151 | 31.75 | 0.9 | 220 | |
| DG153 | 31.75 | 0.9 | 635 | |
| DG155 | 32.5 | 1.25 | 200 | |
| DG155L | 32.5 | 1.25 | 635 | |
| DG159 | 36.4 | 1.2 | 200 | |
| DG159L | 36.4 | 1.2 | 600 | |
| DG156 | 37 | 1.5 | 200 | |

Chainstay

| | | | | |
|--------|--------------|---------|-----|--------------------|
| FX2500 | 22.2 | 0.8/0.6 | 410 | round oval round |
| FX2510 | 18 x 29 oval | 0.8/0.6 | 410 | oval |
| FX2560 | 17 x 27 oval | 0.8/0.6 | 410 | oval - bent 12 deg |

Seatstay

| | | | | |
|--------|--------------|-----|-----|---------------------|
| GX2620 | 14 | 0.6 | 620 | single taper |
| GX2600 | 16 | 0.6 | 560 | double taper |
| GX2610 | 16 | 0.6 | 560 | single taper |
| GX2650 | 16 | 0.7 | 580 | single taper |
| GX2660 | 19 | 0.7 | 580 | single taper |
| GX2655 | 17 x 14 oval | 0.6 | 570 | oval - single taper |

| Part number | Outside Diameter (mm) | Gauge (thickness) mm | Length mm | Description or or butt profile (mm) |
|-------------|-----------------------|----------------------|-----------|-------------------------------------|
|-------------|-----------------------|----------------------|-----------|-------------------------------------|

Reynolds 631

Frame tubes

| | | | | |
|--------|-------|--------------------|-----|------------------------------|
| AX5000 | 25.4 | 0.8/0.5/0.8 | 600 | 100.50.300.50.100 |
| BX5049 | 28.6 | 0.7/0.4/0.7 | 635 | 75.50.280.50.180 |
| BX5050 | 28.6 | 0.8/0.5/0.8 | 635 | 100.50.300.50.135 |
| BX5053 | 28.6 | 0.9/0.6/0.9 | 635 | 75.50.280.50.180 |
| BX5128 | 31.75 | 0.8/0.5/0.8 | 635 | 120.50.300.50.115 |
| BX5125 | 31.75 | 0.9/0.6/0.9 | 635 | 120.50.300.50.115 |
| BX5173 | 34.9 | 0.8/0.5/0.8 | 680 | 120.50.300.50.160 |
| BX5175 | 34.9 | 0.9/0.6/0.9 | 635 | 120.30.320.30.135 |
| BX5190 | 37.3 | 0.9/0.6/0.9 | 635 | 120.50.295.50.120 |
| CX5200 | 28.6 | 0.8/0.55 | 635 | 120.75.435 |
| CX5361 | 28.6 | 0.9/0.6/1.2 bulged | 400 | 150.80.60.50.60 bulge 27.2 |
| CX5362 | 28.6 | 0.9/0.6/1.2 bulged | 450 | 125.80.95.50.100 bulge 27.2 |
| CX5363 | 28.6 | 0.9/0.6/1.2 bulged | 550 | 170.50.155.75.100 bulge 27.2 |
| CX5364 | 28.6 | 0.9/0.6/1.2 bulged | 650 | 190.50.260.50.100 bulge 27.2 |

Shaped top / down tubes

| | | | | |
|--------|---------|-------------|-----|----------|
| AX5605 | 48 x 28 | 0.9/0.6/0.9 | 635 | teardrop |
|--------|---------|-------------|-----|----------|

Reynolds 525

Frame tubes

| | | | | |
|-------|-------|--------------------|-----|---------------------------------|
| AF100 | 25.4 | 0.9/0.6/0.9 | 600 | 100.50.300.50.100 |
| AF101 | 25.4 | 0.8/0.6/0.8 | 600 | 100.50.300.50.100 |
| AF208 | 28.6 | 0.8/0.5/0.8 | 635 | 75.50.280.50.180 |
| AF200 | 28.6 | 1.0/0.7/1.0 | 635 | 75.50.280.50.180 |
| AF201 | 28.6 | 0.9/0.6/0.9 | 635 | 120.50.300.50.115 |
| AF304 | 31.75 | 0.8/0.5/0.8 | 635 | 120.50.300.50.115 |
| AF301 | 31.75 | 0.9/0.6/0.9 | 635 | 120.50.300.50.115 |
| AF501 | 34.9 | 0.9/0.6/0.9 | 635 | 120.30.320.30.135 |
| AF400 | 28.6 | 1.0/0.7 | 635 | 120.75.440 |
| AF401 | 28.6 | 0.9/0.6 | 635 | 120.75.440 |
| AF455 | 28.6 | 0.9/0.6/1.2 bulged | 550 | 170.50.155.75.100 - 27.2 pillar |
| AF457 | 28.6 | 0.9/0.6/1.2 bulged | 635 | 170.50.260.30.125 - 27.2 pillar |

Shaped top / down tubes

| | | | | |
|--------|---------|-------------|-----|----------|
| AF2600 | 50 x 32 | 0.9/0.6/0.9 | 650 | teardrop |
| AF2605 | 48 x 28 | 0.9/0.6/0.9 | 635 | tearfrog |

Head tubes

| | | | | |
|-------|-------|------|-----|--|
| DC151 | 31.75 | 0.9 | 220 | |
| DC155 | 32.5 | 1.25 | 200 | |
| DC159 | 36.4 | 1.2 | 200 | |
| DC156 | 37 | 1.5 | 200 | |

| Part number | Outside Diameter (mm) | Gauge (thickness) mm | Length mm | Description or or butt profile (mm) |
|-------------|-----------------------|----------------------|-----------|-------------------------------------|
|-------------|-----------------------|----------------------|-----------|-------------------------------------|

525 continued

Chainstays

| | | | | |
|--------|--------------|---------|-----|--------------------|
| FC1500 | 22.2 | 0.8/0.6 | 410 | round oval round |
| FC1510 | 18 x 29 oval | 0.8/0.6 | 410 | oval |
| FC1565 | 17 x 27 oval | 0.8/0.6 | 420 | oval - bent 12 deg |
| FB584 | 22.2 | 1.2 | 440 | round oval round |

Seatstays

| | | | | |
|--------|----|-----|-----|--------------|
| GC1625 | 14 | 0.6 | 600 | double taper |
| GC1600 | 16 | 1.6 | 560 | double taper |
| GC1610 | 16 | 0.6 | 560 | single taper |
| GC1670 | 16 | 0.9 | 600 | single taper |
| GC1660 | 19 | 0.7 | 580 | single taper |

Other tubes

| | | | | |
|-------|--------------|-----|-----|--------------------------|
| KC120 | 50 x 25 oval | 0.9 | 760 | tandem base tube - oval |
| KC111 | 38.1 | 1 | 760 | tandem base tube - round |

Steering column

| | | | | |
|-------|------|---------|-----|-----------------|
| HA121 | 25.4 | 22.2 | 280 | threaded 24 tpi |
| HB102 | 25.4 | 2.3/1.6 | 240 | threaded 24 tpi |
| HB103 | 25.4 | 2.3/1.6 | 300 | threaded 24 tpi |
| HB113 | 25.4 | 2.3/1.6 | 300 | no thread |
| HB104 | 25.4 | 2.3/1.6 | 400 | threaded 24 tpi |
| HB114 | 25.4 | 2.3/1.6 | 400 | no thread |
| HB131 | 25.4 | 2.9/1.6 | 240 | threaded 24 tpi |
| HB132 | 25.4 | 2.9/1.6 | 280 | threaded 24 tpi |
| HB140 | 28.6 | 2.3/1.6 | 215 | threaded 26 tpi |
| HB145 | 28.6 | 2.3/1.6 | 300 | no thread |

Reynolds butted "R" fork blades

| | | | | |
|-------|----------------|---------|-----|------------------------------|
| EB475 | 29 x 16 oval | 1.2/0.7 | 395 | bent, rake 15x45mm (touring) |
| EB465 | 29 x 16 oval | 1.2/0.7 | 395 | straight |
| EB708 | 27.5 X 20 oval | 1.0/0.5 | 370 | straight |
| EB716 | 27.5 x 20 oval | 1.0/0.5 | 370 | bent, rake 16x30mm (road) |
| EB720 | 27.5 X 20 oval | 1.1/0.8 | 400 | straight |
| EB711 | 27.5 x 20 oval | 1.2/0.7 | 395 | straight |
| EB713 | 27.5 x 20 oval | 1.2/0.7 | 395 | bent, rake 15x45mm (touring) |
| EB712 | 27.5 x 20 oval | 1.4/0.9 | 400 | straight |

| Part number | Outside Diameter (mm) | Gauge (thickness) mm | Length mm | Description or or butt profile (mm) |
|-------------|-----------------------|----------------------|-----------|-------------------------------------|
|-------------|-----------------------|----------------------|-----------|-------------------------------------|

TITANIUM FRAME TUBES

Reynolds 3/2.5 seamless Titanium

Frame tube

| | | | | |
|-------|-------------------------|-------------|-----|-------------------------|
| BT129 | 31.75 | 0.9/0.7/0.9 | 580 | 75.50.280.50.125 |
| BT122 | 31.75 | 0.9/0.7/0.9 | 625 | 75.50.280.50.170 |
| BT128 | 36.4 | 0.9/0.7/0.9 | 680 | 120.50.300.50.160 |
| CT158 | 31.75od taper to 27.2id | 0.9/0.7/0.9 | 625 | 75(taper).50.280.50.170 |

Chainstay

| | | | | |
|-------|------------|-----|-----|------------------|
| FT123 | 22.2 | 0.9 | 410 | round oval round |
| FT126 | 17x27 oval | 0.9 | 400 | straight |

Seatstay

| | | | | |
|-------|----|-----|-----|--------------|
| GT127 | 16 | 0.8 | 575 | single taper |
| GT123 | 19 | 0.7 | 570 | single taper |

Reynolds seamless 6/4 titanium

Frame tubes

| | | | | |
|-------|------|---------------|-----|-------------------|
| BT628 | 36.4 | 0.85/0.7/0.85 | 685 | 120.65.270.65.165 |
| BT627 | 34.9 | 0.85/0.7/0.85 | 685 | 120.65.270.65.165 |
| BT622 | 31.7 | 0.85/0.7/0.85 | 650 | 120.50.300.50.130 |
| CT659 | 31.7 | 0.8/0.64 | 635 | 125.75.432 |

chainstay

| | | | | |
|-------|--------------|------|-----|-----------------|
| FT616 | 31 x 20 oval | 0.77 | 430 | tapered to 18mm |
|-------|--------------|------|-----|-----------------|

seatstay

| | | | | |
|-------|-------|------|-----|--------------|
| GT623 | 19.05 | 0.77 | 520 | double taper |
|-------|-------|------|-----|--------------|

Reynolds 7005 T6 and 6061 aluminium

Reynolds 6061 & 7005 are available on special order only. Subject to minimum order quantities